


Unit Bearing Fan Motors

Features:

- Aluminum & Cast Iron
- All Models Include Vibration Dampening Hub Washer, Speed Nut and 4 Mounting Screw
- Continuous Duty, Air Over
- Horizontal & Shaft Up Mounting Only
- 60/50 Hz
- Shaded Pole
- 115 & 230 Volt
- Totally Enclosed
- Impedance Protected
- UL & CSA Recognized



CAST IRON - TWO MOUNTING FEET

Watts Output	RPM	Volts	Amps	Stock Number	Rotation	Rear Mounting Holes	"A" Dim.	Emerson No.	Notes
2	1550	115	0.22	UB02CWL2F	CWLE	3	2.52		
4	1550	115	0.29	UB04CWL2F	CWLE	3	2.52	2115	
4	1550	115	0.29	UB04CCL2F	CCWLE	3	2.52	2103	
4	1550	230	0.15	UB04CWH2F	CWLE	3	2.52	2123	
4	1550	230	0.15	UB04CCH2F	CCWLE	3	2.52	2122	
5	1550	115	0.34	UB05CWL2F	CWLE	3	2.52	2119	
6	1550	115	0.40	UB06CWL2F	CWLE	3	2.74	2117	
6	1550	115	0.36	UB06CCL2F	CCWLE	3	2.74	2116	
9	1550	115	0.55	UB09CWL2F	CWLE	3	2.74	2108	
9	1550	115	0.55	UB09CCL2F	CCWLE	3	2.74	2118	
9	1550	230	0.27	UB09CWH2F	CWLE	3	2.74	2110	
9	1550	230	0.27	UB09CCH2F	CCWLE	3	2.74	2109	
16	1550	115	1.0	UB16CWL12F	CWLE	3	3.11	2112	
16	1550	115	1.0	UB16CCL12F	CCWLE	3	3.11	2111	
16	1550	230	0.50	UB16CWH12F	CWLE	3	3.11	2114	
16	1550	230	0.50	UB16CCH12F	CCWLE	3	3.11	2113	

ALUMINUM - TWO MOUNTING FEET

Watts Output	RPM	Volts	Amps	Stock Number	Rotation	Rear Mounting Holes	"A" Dim.	Emerson No.	Notes
4	1550	115	0.29	UB04CWLA2F	CWLE	5	2.25	D554	
4	1550	115	0.29	UB04CCLA2F	CCWLE	5	2.25	D555	
5	1550	115	0.34	UB05CWLA2F	CWLE	5	2.25	D582	
5	1550	115	0.34	UB05CCLA2F	CCWLE	5	2.25	D583	
6	1550	115	0.40	UB06CWLA2F	CWLE	5	2.50	D558	
6	1550	115	0.40	UB06CCLA2F	CCWLE	5	2.50	D559	
9	1550	115	0.50	UB09CWLA2F	CWLE	5	2.50	D562	
9	1550	115	0.50	UB09CCLA2F	CCWLE	5	2.50	D563	
9	1550	230	0.25	UB09CWA2F	CWLE	5	2.50	D564	
9	1550	230	0.25	UB09CCHA2F	CCWLE	5	2.50	D565	

Notes:

See parts & accessories on page 20

www.electricmotorwarehouse.com