






ELECTRIC MOTOR WAREHOUSE

Dayton

Universal Type AC/DC 115 Volts 60hz.

	Model #	HP	Rotation	RPM	Bearings	Shaft	Amps
	2M066	1/15	CCW	5,000	Sleeve	1" X 1/4" x 1" Double Shaft	1.2
	Overall Length = 5-7/16" Length Less Shaft = 4-7/16" Body Dia. = 2-3/4" Base 2 3/16" x 3" O.C. Mounting						
	2M033	1/15	CCW	5,000	Sleeve	1/4" x 3/4"	1.2
	Side with Two Tapped Size 10-32 Holes, 2 3/16" O.C. on One or Both Sides Mounting Overall Length = 5-3/16" Length Less Shaft = 4-7/16" Body Dia. = 2-3/4"						
	2M277	1/15	CCW	5,000	Sleeve	1/4" x 3/4"	1.2
	Side with Two Tapped Size 10-32 Holes, 2 3/16" O.C. on One or Both Sides Mounting Overall Length = 5-3/16" Length Less Shaft = 4-7/16" Body Dia. = 2-3/4"						
	2M057	1/15	CCW	5,000	Ball	5/16" x 7/8"	1.2
	Side with Two Tapped Size 10-32 Holes, 2 3/16" O.C. on One or Both Sides Mounting Overall Length = 5-3/16" Length Less Shaft = 4-7/16" Body Dia. = 2-3/4"						
	2M034	1/15	CW	5,000	Sleeve		

	Side with Two Tapped Size 10-32 Holes, 2 3/16" O.C. on One or Both Sides Mounting Overall Length = 5-3/16" Length Less Shaft = 4-7/16" Body Dia. = 2-3/4"				1/4" x 3/4"	1.2
	2M037	1/10	CCW	8,000	Ball	
	Side with Two Tapped Size 10-32 Holes, 2 3/16" O.C. on One or Both Sides Mounting Overall Length = 5-3/16" Length Less Shaft = 4-7/16" Body Dia. = 2-3/4"				1/4" x 7/8"	1.5
	2M139	1/5	CCW	10,000	Sleeve	
	Stud with Two Size 8-32 Threaded Studs Extending Out Shaft Endshield, 2 7/16" O.C. Overall Length = 5-1/2" Length Less Shaft = 4-1/2" Body Dia. = 3-3/8"				5/16" x 1"	2.9
	2M145	1/2	CCW	10,000	Ball	
	Mounting: Bottom with Four Tapped Size 10-32 Holes, 2" x 2 13/16" O.C. Overall Length = 7-7/16" Length Less Shaft = 6-3/16" Body Dia. = 3-3/4 x 3-1/2" Replacement Brushes = 1R393				3/8" x 1 3/16"	6.3
	2M191	1	CCW	10,000	Ball	
	Mounting: Face with Four Tapped Size 10-32 Holes, 3 1/4" OC 90 Degrees Apart Overall Length = 9-1/32" Length Less Shaft = 7-25/32" Body Dia. = 3-7/8"				7/16" x 1 1/4"	12.1