

# ELECTRIC MOTOR WAREHOUSE

## Fireplace Blower, Pellet Stove Auger Motor Woodstove Replacement Blowers


|   | Fireplace Brand/Model  | Description  | Catalog # |
|---|--|--|-----------|
|    | Buck Stove Blower Motor<br>115 volt, 3-speed, 1550RPM<br>Bolt Circle = 2.85"   | R22CCW270ZD 7163-6045 U9522<br>Fan Cooled, there is a fan on back end of motor with a cover over it (shroud full length of motor)<br>Single shaft 5/16" X 2.5"<br>Motor Length without shaft = 4"<br>Motor Diameter 3.9"; rotation = CW<br>.9 amps, 115 Volts  | D1138     |
|    |  | R22CW206MD U9520<br>Double shaft: 2" x 5/16" x 1 1/8"<br>Motor Length without shaft = 2 13/16"<br>Motor Diameter 3.3"; rotation = CW<br>.88 amps, 115 Volts  | D1139     |
|   | 1/60hp, 3000RPM<br>115 Volt, 0.6 amps<br>3.3" Diameter Motor<br>Motor Case Length 3.5"<br>Fan = 4 .75" Diameter<br>Mounting Plate = 5.75"<br>Bolt Hole Centers = 5 3/8"<br>shaft = 5/16" x 1 7/8"<br>Rotation = CW facing shaft<br>Includes gasket, fan blade & plug | Pellet Stove Blower Motor<br>Whitfield - Quest 12026011, 13656011, 10-1111 G<br>Breckwell, Travis (Avalon & Lopi)<br>Quadra-Fire, Fasco 7021-9129, 702111469<br>7121-7001, 7021-8786, 7021-11469<br>J238-150-15288<br><br>J238-150-1518, J238-112-11226, 119289-00, 076002B<br>blower motor with mounting plate only, not complete housing | HB-RBM120 |
|  | 1/65 hp<br>.50 amps, 115 Volts<br>2 Speed, 1500 RPM<br>3.3" Diameter Motor<br>Rotation Clockwise Facing Shaft<br>Shaft: 5/16" x 1.6"<br>Motor Length: 3.5"<br>Shaded Pole Motor<br>Totally Enclosed  | Acorn Wood Stove 71730867, 2868509042<br>Selkirk 605850M0  | HM-R250   |
|   | 1/70 115 Volts; 0.92 amps<br>3 Speed; 1300 RPM   |  |           |

|   |   |   |          |
|---|---|---|----------|
|    | 1/250 HP, 1000 RPM<br>2.5" Motor Case Length<br>3.3" Motor Diameter<br>Sleeve Bearings<br>Shaft: 3"x5/16"x3.8 | Elmira Wood Stove 1500, 1600  | HM-R489  |
|    | Hunter Wall Heater 917250   | 1/250 HP, .30 amps, 115 Volts<br>1500 RPM, 1-Speed<br>CCW Rotation<br>Sleeve Bearings<br>Round discharge-no flange  | HB-RB91  |
|    | CFM-HE30<br>CFM-HE32<br>Majestic InstaFlame<br>Replaces 53311 (For HE30TN)                                    | Comes with mounting base plate<br>No power cord, 130 CFM, 1250RPM<br>Overall Length = 14" Height 4"<br>Flange opening = 9.5", .86 amps  | R7-RB63  |
|    | CFM-FA20<br>CFM-FK24<br>CFM-RHE32<br>Travis (gas)<br>Majestic InstaFlame HE30                                 | Blower only, no power cord<br>120 CFM, 1250 RPM, .86 amps<br>Overall length= 13" Width 4.5", Height 3.8"<br>Flange Opening = 9.5"   | R7-RB64  |
|    | CFM-FK30  | Includes 2' power cord, magnetic strips<br>70 CFM, 1250RPM, .86 amps<br>Overall Length = 8" Height = 4.5"<br>Flange Opening = 4.8"  | R7-RB130 |
|    | CFM-HE20<br>Majestic InstaFlame<br>Rotom R7-RB82  | Blower only, 110 CFM, 1400 RPM,<br>no power cord, .75 amps<br>Overall Length = 10.5" Height = 3.75"<br>Flange Opening = 7.1" RIGHT HAND MOTOR   | R7-RB82  |
|   | Continental GZ552 Gas Fireplace<br>Napolean GZ552 Gas fire Place<br>Kingsman Z33FK Gas                        | Blower only, 160 CFM, 2400 RPM<br>no power cord, .75 amps<br>Overall Length = 10.5", Height = 3 .75"<br>Flange opening = 7.1" LEFT HAND MOTOR   | R7-RB61  |
|  | Continental GZ550 Gas Fireplace<br>Napolean GZ550 Gas fire Place  | Includes blower, wiring harness, speed control,<br>thermoswitch, power cord and mounting base.<br>110CFM, 1400RPM<br>Overall Length = 10.5" Height = 3.75"<br>Flange Opening = 7.1"                       | R7-RB58  |
|  | Continental GZ552 Gas Fireplace<br>Napolean GZ552 Gas fire Place  | Includes blower, mounting base plate, speed control<br>110CFM, 1400RPM<br>Overall Length = 10.8" Height = 3.75"<br>Flange Opening = 7.1"  | R7-RB59  |
|  | Continental GZ552 Free<br>Standing<br>Napolean GZ552 Free Standing  | Includes blower, mounting bracket, speed control, power<br>cord. 2800RPM, 110CFM, .72 amps<br>Mounted on sheet metal case (3 sided)<br>Overall case length = 14" Height= 3.75"<br>Flange opening = 7 1/8" | R7-RB62  |

|   |   |  |           |
|---|---|--|-----------|
|    | Dutchwest FK26<br>2465 Direct Vent<br>2467 Natural Vent<br>Stardance FK26<br>SNV30 Natural Vent | Includes blower, mounting base, variable speed control cord with 3-prong plug<br>Overall length = 13" Height 5.75" Width 5"<br>115 CFM, 2400RPM, .092 amps   | R7-RB27   |
|    | Hearth & Home Technologies<br>Quadra-Fire FKGAS<br>(Stove Blower)                               | Includes Blower, housing, variable speed control, thermo switch<br>Power Cord with three-prong plug<br>Ball Bearings<br>0.92 Amps; 115 Volts; 2400 RPM; 115 CFM<br>Blower Size - 12.8" Length x 4.6" Height x 4.3" Width<br>Blower Wheel 3" x 4" | HB-RB81   |
|    | Heatilator FK4, GFK24   | Includes blower, 3' power cord, velcro strips, speed control, thermal switch.<br>130 CFM, 1250 RPM<br>Flange Opening = 9.5" 0.86 amps<br>Overall Length = 13" Height = 4.50"<br>width = 4 5/16" Motor on right side                              | R7-RB74   |
|    | Heatilator FK21, GFK21<br>Novus 30<br>Security UZY3   | Includes blower, speed control, Thermal switch and power cord with 3-prong plug.<br>80 CFM, 1800 RPM, .75 amps<br>Overall Length = 8" Height 4.5"<br>Flange Opening = 4.75", (motor on left)   | R7-RB21   |
|    | Heatilator FK21, GFK21<br>Security UZY3   | Blower only, no power cord<br>66 CFM, 1800 RPM<br>.75 amps, (motor on right)<br>Overall Length = 8.5" Height 3 5/8"<br>Flange opening = 4.75"  | R7-RB66   |
|   | Heat N Glow GFK-160A<br>7002-1241<br>Royal GFK-160  | Includes blower, cord, speed control, thermostwitch, magnets<br>125 CFM, 2400 RPM, 0.92 amps<br>Skelton Motor<br>Overall length = 13.0" x 5" height<br>2 openings: 1" x 4 7/8"   | R7-RB168  |
|  | Heat N Glow GFK-160A<br>Regency Wood Stove Insert<br>846515<br>Royal GFK-160<br>Jakel           | Same as R7-RB168 except it is <u>Blower only</u><br>125 CFM, 2400 RPM, 0.94 amps<br>Skelton Motor, cord with 2-prong plug<br>Mounting Bracket with magnets<br>overall length = 13.0" x 5" height<br>2 openings: 1" x 4 7/8"                      | R7-RB168B |
|  | Hunter 770, HDS2000<br>HDS3000, HF130, HDV31<br>MGDV31, SFVD20                                  | Includes blower, wiring, speed control and thermostwitch. 130 CFM, .86 amps, 1250RPM<br>Overall length = 13", height 4"<br>Flange opening = 9.5"   | R7-RB68   |
|   |   | Blower Only, no power cord   |           |

|   |   |   |          |
|---|---|---|----------|
|                        | Hunter 770, HDS2000, HDS3000<br>HF130, HDV25003DV<br>Heatilator FK4<br>Regency P33R-2/P36-3/P36D<br>Lennox FK2 FAN-SC96K14<br>Kingsman Z35FK, Z36FK | Blower Only, no power cord<br>120 CFM, 1200 RPM 0.86 amps<br>Overall Length 13", Height = 3.8", Width = 4.5"<br>Flange Opening = 9.5"<br>Motor on left side<br>(Squirrel cage larger than original Lennox)<br>(same size blower as R7-RB74) | R7-RB84  |
|                        | Hunter F125H, HWF30, HDV30  | Blower only, no power cord<br>150 CFM, 1200 RPM .75 amps<br>Overall Length = 15.8", Height 3.8"<br>Flange opening = 11.75"  | R7-RB79  |
|                        | Hunter, Napolon, Valor<br>Fasco 7063-7735   | Exhaust Blower, includes 3 prong plug<br>1/125 hp, 1500RPM, 0.36 amps, 115 volts<br>Outlet Flange size: 2 5/8" x 1 3/16"<br>Overall Height: 8 5/8"<br>7073-1394   | HB-RB735 |
| <br>Low Profile Blower | Kingsman<br>Fits all 33,35, 37,48   | Includes blower, magnetic mounting, wiring, variable speed control, thermostats, power cord, Skelton Motor<br>overall length = 13.25" x 5" height<br>2 openings: 1" x 4 7/8"  | R7-RB38  |
|                        | Kingsman<br>Z35FK, FDV350, FDV5000, 4000  | Blower, Mounting Base<br>Variable Speed Control, Power Cord<br>50 Watts, 0.86 Amps, 115 Volts<br>1250 RPM, 130 CFM<br>Blower Size - 12.9" Length x 4.3" Height x 3.6" Width<br>Blower Wheel: 2.6" x 9.4"                                    | HB-RB35  |
|                      | Kingsman Z36FK  | Blower, Mounting Base<br>Thermal Switch Assembly<br>Variable Speed Control, Power Cord<br>50 Watts, 0.86 Amps, 115 Volts<br>1250 RPM, 130 CFM<br>Blower Size - 12.9" Length x 4.3" Height x 3.6" Width<br>Blower Wheel: 2.6" x 9.4"         | HB-RB36  |
|                      | Kingsman Z33K   | Blower, Mounting Base<br>Thermal Switch Assembly<br>Variable Speed Control, Power Cord<br>42 Watts, 0.75 Amps, 115 Volts<br>1250 RPM, 130 CFM<br>Blower Size - 10.5" Length x 4.3" Height x 3.6" Width<br>Blower Wheel: 2.6" x 7.1"         | HB-RB37  |
|   |   | Blower only and 3' power cord<br>Flange Opening = 9.5" 2800 RPM   |          |

|   |  |  |          |
|---|--|--|----------|
|    | Majestic FK12  | Flange Opening = 9.5", 2800 RPM<br>130 CFM, 0.86 amps<br>Overall Length 13" Height = 3 7/8"<br>No mounting plate-has magnets<br>same size blower as R7-RB65  | R7-RB12  |
|    | Majestic FK24  | Includes blower, 5' cord, speed control<br>thermoswitch. 130 CFM, 2800 RPMs<br>Controls mounted in metal box.<br>Blower mounted on flat plate: 15" x 4"<br>2 Rubber cushions mounted to bottom of plate<br>Plate has mounting holes 14" O.C.<br>Flange Opening = 9.5" 0.70 amps<br>Overall Blower Length = 13", Height = 3 .75", Width =<br>4.5" | R7-RB65  |
|    | Majestic FK4, GFK4   | Includes blower, 3' cord, velcro strips,<br>speed control. 130 CFM, 1250 RPMs<br>Flange Opening = 9.5" 0.86 amps<br>Overall Length = 13" Height = 4.8"<br>Not mounted on a plate   | R7-RB74  |
|    | Nordica  | Blower Only, no power cord<br>220 CFM, 2600 RPM 1.35 amps<br>Overall Length 17.6", Height = 4.24", Width = 3"<br>Flange Opening = 13"<br>Motor on left side  | R7-RB513 |
|    | Nordica  | Blower Only, no power cord<br>73 CFM, 1800 RPM .38 amps<br>Overall Length 13", Height = 3.7", Width = 3.2"<br>Flange Opening = 9.8"<br>Motor on left side  | R7-RB571 |
|   | Nordica<br>Nordica B150<br>Traditional 1600-2199<br>Rustic 1600-2100                             | Blower Only<br>0.92 AMPS, 115V, 2400 rpm (one speed); 125 CFM<br>Rotation = CCW, Ball Bearing<br>Dimensions: 12.8" x 4.6" x 4.3"<br>Blower wheel: 3" x 4"  | HB-RB166 |
|  | Northern Flame FK24<br>A232, D232<br>Top Vent Direct: DBT33, DBT36<br>DBT39, DBR33, DBR36, DBR39 | Includes blower, 5' cord, speed control<br>thermoswitch. 130 CFM, 2800 RPMs<br>Controls mounted in metal box.<br>Blower mounted on flat plate: 15" x 4"<br>Plate has mounting holes 14" O.C.<br>Flange Opening = 9.5" 0.70 amps<br>Overall Blower Length = 13", Height = 3 .75"  | R7-RB65  |
|  | Osburn KA-108  | blower includes mounting plate with grommets.<br>130 CFM, 1250 RPMs, .86 amps<br>Flange opening = 9.5"<br>Overall Length = 13" Height = 4"   | R7-RB108 |
|   |  | Includes 2-speed blower and box with cord.<br>Overall Length = 20 1/4" Height 4 3/4"   |          |

|   |   |  |          |
|---|---|--|----------|
|    | Osburn FD006-1600 (Inserts)<br>1800, 2200, 2400 (Stoves)  | Overall Width = 6"<br>Flange opening = 1.5"<br>width without "L" mount = 4 5/8"<br>"L" Mount has 2 sets of mounting holes<br>spaced 10" on center  | R7-RB006 |
|    | Osburn FD006-1600 Insert<br>1800, 2200, 2400 Stove<br>Nordica Fireplace, Valley<br>Comfort,<br>Regency 910-157/P (wood)<br>Pacific Energy Esteem 5053-947 | Blower only - 2 Speed Motor<br>80/135 CFM, 2800 RPM, .92 amps<br>Skelton Motor, power leads only, no switch<br>overall length = 13.0" x 4.25" height<br>2 openings: 1"x 4 7/8"   | R7-RB167 |
|    | Pacific Energy Esteem<br>Fan Kit 5053-947   | Includes blower, wiring, variable speed control switch<br>mounting base with rubber grommets<br>115CFM, 2400 RPM, .92 amps<br>Overall Length = 13" x 4.6" height x 4.3" width  | R7-RB50  |
|    | Polaris PG200   | Blower only, 105CFM, 2900 RPM<br>.77 amps<br>Overall Length = 10", Height 3.75"<br>Flange Opening = 7 3/8"   | R7-RB944 |
|    | Quadra Fire<br>Free Standing Woodstove Blower   | Blower Housing, built in speed control<br>8' cord with 3 prong plug. 125 CFM, 2400 RPM<br>Overall Length 14" x 5" height x 6" width  | R7-RB83  |
|    | Regency<br>C33-2 Classic<br>F1100, F2400M, F3100  | Blower only - 2 Speed Motor<br>80/135 CFM, 2800 RPM, .92 amps<br>Skelton Motor, no power cord<br>Overall length = 13.0" x 4.25" height<br>2 openings: 1"x 4 7/8"   | R7-RB167 |
|   | Regency<br>P33-3, P33R-2,   | Blower Only, no power cord<br>120 CFM, 1200 RPM 0.86 amps<br>Overall Length 13", Height = 3 .8"<br>Flange Opening = 9.5"<br>Motor on left side<br>(Squirrel cage larger then original Lennox)<br>(same size blower as R7-RB74)   | R7-RB84  |
|  | Regency<br>432917 (Fan), P33, P36, P48<br>National Gas 3624N, 24663<br>Travis 99000153<br>Heatilator GFK4, FK4  | Includes blower, magnetic mounting, thermal switch<br>assembly with mounting magnets, variable speed<br>control with magnetic mounting -cord with three prong<br>plug. 130CFM, 1250 RPM<br>Overall Length 13", Height = 3 3/4"<br>Flange Opening = 9.5"<br>Motor on right side | R7-RB39  |
|  | Security UZY4 Wood Fireplace<br>Heatilator  | One blower only, 80 CFM, 1800 RPM, .40 amps<br>Mounting base plate with grommets<br>Overall length = 8" Height 3.75"<br>Flange Opening = 4.75" x 1 7/8"<br>(blowers same as R7-RB267)  | R7-RB67  |
|   |   | 2 blower fan kit, wiring harness with  |          |

|   |   |  |           |
|---|---|--|-----------|
|  | Security UZY4 Wood Fireplace            | three prong plug, thermostwitch, Magnets.<br>80 CFM, 1250 RPM .75 amps<br>Overall length = 8.25 " Height 3.75"<br>Flange Opening = 4.75" x 1 7/8"<br>(blowers same as R7-RB67) | R7-RB267  |
|  | Rotom Double Transflo Blower<br>29"     | Blower only, 360 CFM, 2900 RPM<br>Overall length = 29" Height 3.75"<br>Flange Openings = 12.5" x 2" (double)   | R7-RB96   |
|  | Pacific Energy                          | .92 amps, 115 Volts; 2400 RPM, 1-Speed<br>125 CFM; Ball Bearings<br>17.5" x 4.75" x 4.3"; Blower Wheel 3" x 4"   | HB -RB179 |
|  | Regency<br>432-917, P33, P36, P36D, P48 | .86 amps, 115 Volts; 1250 RPM, 1-Speed<br>130 CFM; Ball Bearings<br>Blower: 12.9" x 4.3" x 3.6"<br>Wheel: 65mm x 240mm   | HB-RB32   |
|  | RSF FO-FDHB5-N                          | 1.3 amps, 115 Volts<br>1300 RPM-1-Speed<br>225 CFM; Ball Bearings<br>Blower: 24.5"(L) X 4 7/8"(D) X 4 1/2"(H)<br>Wheel: 65mm x 240mm<br>Flange openings: 9.5"                  | HB-RB53   |
|  | Fireplace Blower Fan 115 Volt           | 62 Watt, 1.1 amp, 115 Volt<br>1200 RPM, 150 CFM<br>CW Rotation; Sleeve Bearings<br>Blower: 15.7" x 4.3" x 3.6"<br>Wheel: 2.6" x 11.8"<br>Flange opening 11.8"                  | HB-RB69   |